

neoom®

# BOOGIE

The intelligent design  
charging station.



## WELL-EQUIPPED FOR THE FUTURE

neoom® BOOGIE is characterized by its modern design and easy handling. BOOGIE can be controlled via smartphone using QR code or RFID technology and is suitable for private and public use. The compatibility with common billing systems makes the BOOGIE ready for future requirements.

## THE DYNAMIC CHARGING SOLUTION

neoom® BOOGIE provides a power up to 2x 22 kW and comes with a Type 2 connector or an optional 4m spiral cable. Thanks to its dynamic load management higher charging power, lower energy consumption and reduced operating costs can be achieved.



Modern design and intelligent technology in a masterpiece.

## TECHNICAL DATA

Maximum connected load	2 x 22 kW, 3-phase, 400V
Options	4 m charging cable Type 2 or socket
Load management	Static or dynamic, master-slave function
Communication	RFID, Webinterface, OCPP
Interfaces	Ethernet RJ45 & Modbus RS485
Fuse protection	Direct current failure detection 6mA IEC 61851 Load contactor welding detection, fault current circuit breaker Type A
Meter	MID for billing per charging point
Dimensions (w x h x d)	570 mm x 1624 mm x 170 mm
Safety class	IP44
Environmental temperature	-20 °C to 55 °C
Network	GSM / LAN
Options	Labeling, intelligent fault current circuit breaker, individual QR-Code